

A10-M Rubidium Frequency Reference

- Low Phase Noise
- Aging $<5 \times 10^{-10}$ per year
- High Precision Atomic Clock
- Two years warranty



Description

The Quartzlock A10-M rubidium frequency reference is a 10 MHz, high-stability Rubidium frequency standard with flexible output options and very low cost of ownership primarily for production test of quartz oscillators and RF instrumentation frequency referencing. The A10-MX incorporates the latest high stability and low drift designs. It may also have both 5MHz and 10MHz outputs presented on the front panel to align with A7-MX Signal Stability Analyzer reference input.

Applications

- Frequency Calibration
- Telecom Network Synchronization
- Broadcast – Radio & TV & Satellite Communications
- HDTV
- Production Test Reference for instrumentation
- Microwave Test Bench or Test Solution

Features

Output signals: Sine wave & CMOS/TTL

Multiple Output options: 5 to 100MHz

Custom Frequency Outputs: 2 - 125MHz, 1PPS

Low Noise Floor: -170dBc at 10KHz offset

Front panel outputs

Exceptionally low drift/aging and high stability per hour/day

Stability	8×10^{-13}
------------------	---------------------

Magnetic field sensitivity	$2 \times 10^{-11}/\text{Gauss}$
-----------------------------------	----------------------------------

Frequency trim range	2×10^{-9}
-----------------------------	--------------------

Optional disciplined to external 1PPS, or 10MHz

Harmonic distortion	$< 30\text{dB}$ (for 5 MHz output)
----------------------------	------------------------------------

Non-harmonic distortion	$< -100\text{dB}$ in the range from 10Hz to 10kHz
--------------------------------	---

A10-M Specification

Outputs <i>See options</i>				
5 & 10MHz	+7dBm into 50 Ohms, 0.5V _{rms}			
Connector	BNC (Standard), SMA (specify)			
Frequency Stability <i>Allan Deviation</i>				
Frequency	Options A		Options B	
	10MHz	5MHz	10MHz	5MHz
$\tau = 1s$	$\leq 2 \times 10^{-12}$	$\leq 1 \times 10^{-12}$	$\leq 8 \times 10^{-13}$	$\leq 7 \times 10^{-13}$
$\tau = 10s$	$\leq 3 \times 10^{-12}$	$\leq 2 \times 10^{-12}$	$\leq 4 \times 10^{-12}$	$\leq 4 \times 10^{-12}$
$\tau = 100s$	$\leq 5 \times 10^{-12}$	$\leq 4 \times 10^{-12}$	$\leq 3 \times 10^{-12}$	$\leq 3 \times 10^{-12}$
Phase Noise (SSB)				
Frequency	Options C		Options D	
	10MHz	5MHz	10MHz	5MHz
1Hz	-110 dBc	-115 dBc	-117 dBc	-123 dBc
10Hz	-135 dBc	-138 dBc	-140 dBc	-145 dBc
100Hz	-145 dBc	-152 dBc	-152 dBc	-153 dBc
1 kHz	-155 dBc	-154 dBc	-155 dBc	-155 dBc
10KHz	-158 dBc	-155 dBc	-158 dBc	-158 dBc
Harmonics			Options E	
	<-40dBc	<-40dBc	<-50dBc	<-50dBc
Spurious				
100 KHz BW	<-100dBc	<-100dBc	<-100dBc	<-100dBc
Aging (After 30 days)				
Frequency	10MHz	5MHz		
<i>Per day</i>	5×10^{-12}	1×10^{-12}		
<i>Per Month</i>	5×10^{-11}	4×10^{-11}		
<i>Per Year</i>	5×10^{-10}	4×10^{-10}		
Frequency accuracy				
Accuracy at shipping 5×10^{-11}				
Frequency retrace				
After 1 hours of continues operation 3×10^{-11}				
Frequency Adjustment				
Mechanical	$\pm 2 \times 10^{-9}$	Optional		
Electrical	$\pm 2 \times 10^{-9}$	Control voltage 0 to +5V		
Warm up time				
<6 minutes, time to lock				
<7 minutes to 1×10^{-9} at room temperature 25°C				

Included with shipment: Calibration certificate, Certificate of Conformance, product test sheet and 24 month warranty.

Environmental		
<i>Temperature :</i>	Operating	-20°C +60°C
	Storage	-40°C +80°C
<i>Temp stability :</i>	-20°C +60°C	1×10^{-9}
<i>Relative humidity :</i>	95% non-condensing	
<i>Magnetic Field sensitivity :</i>	2×10^{-11} Gauss	
<i>Atmospheric pressure :</i>	-60m –4000m $< 2 \times 10^{-11}$ Per mbar	
<i>Approximate MTBF :</i>	100,000 Hrs, Stationary	
<i>Dimensions :</i>	88mm (3.5") 2U 19" rack mount	
Power supply		
<i>AC power:</i>	90-245V AC, 50Hz	
<i>Optional redundancy switch:</i> see option 00		
Seamless battery back-up switch		
Data output & monitoring		Options X
RS232, 9600 baud rate	USB	Ethernet
Built-in options		
Option 00:	Redundant switchover for external power back-up	
Option 02:	Output 2048kHz	
Option 03:	Output 1544kHz	
Option 04:	13MHz Output	
Option 05:	TTL Output	
Option 06:	1PPS Output	
Option 07:	10.24MHz Output	
Option 08:	10.23MHz Output	
Option 09:	Add 6 Output Distribution Card	
Option 10:	26MHz Output	
Option 18:	Extended warranty to 3 years	
Option 20:	Discipline to external GPS 1PPS or 10MHz input	
Option 21:	2 x 1PPS Output	
Option 42:	Low noise floor -170dBc at 10KHz	
Option 51:	Rack Mount 19" 1U	
Option 52:	Rack Mount 19" 2U	
Option 53:	Rack Mount 19" 3U	
Option 62:	AC Input 110V	
Option 64:	DC input: Specify +12V, +24V, +48V or +60V	
Option 75:	Add internal battery, up to 4 hours of battery life.	

Contact us to configure this product to meet your requirement.
Designed and manufactured in the U.K.

The Quartzlock logo is a registered trademark.

Quartzlock continuous improvement policy: spec subject to change without notice and not part of any contract.

Copyright © 2017. Issue 01.02