

# Portable Rubidium Frequency Reference

## Features

- Compact light weight portable for a wide range of application
- Sine wave or CMOS/TTL output
- Accuracy of  $5 \times 10^{-11}$
- 10 hours battery running time
- Available 1 to 8 outputs
- Two years warranty



E10-P: Standard configuration



E10-P configured with option 09

## Description

Compact simple to install, portable frequency reference for use as a general purpose 10MHz rubidium frequency standard. This portable Rubidium frequency standard will operate from an External 12VDC supply or its Internal Batteries. For remote site operation i.e. cellular BTS the E10-P may run from the cigarette lighter socket to arrive fully charged the internal capacity batteries. The E10-P incorporates the latest high stability and low drift designs. It can be configured to frequencies from 1 to 100MHz outputs presented on the front or rear panel.

## Applications

- Remote site frequency reference for cellular BTS & satellite ground station
- Telecom Network Synchronization
- Broadcast – Radio & TV & Satellite Communications
- Microwave Test or Test Solution
- Field service & production test

## Related frequency reference products

- **A10-M**: Low Noise 1U 19" rack mount Rubidium Frequency standard up to 12 output, 1 to 100MHz
- **A1000** : Low Noise 2U 19" rack mount Rubidium Frequency standard up to 24 output, 1 to 100MHz
- **E10-LN**: Low phase noise Rubidium oscillator module
- **E10-Y**: Low Phase Noise Desktop Rubidium frequency reference, 1 to 8 outputs
- **E10-X** : Desktop & Bench top Frequency reference 1 to 4 outputs

## E10-P Specification

### Outputs *See options*

10MHz	+10dBm into 50 Ohms, 0.7V <sub>rms</sub> (Specify for 75Ω load)
Connector	BNC (Standard), SMA (specify)
No. outputs	1-8

### Frequency Stability *Allan Deviation*

	Options A	Options B
Frequency	10MHz	10MHz
$\tau = 1s$	$\leq 8 \times 10^{-11}$	$\leq 2 \times 10^{-12}$
$\tau = 10s$	$\leq 3 \times 10^{-11}$	$\leq 3 \times 10^{-12}$
$\tau = 100s$	$\leq 8 \times 10^{-12}$	$\leq 6 \times 10^{-12}$

### Phase Noise (SSB)

	Options A	Options B
Frequency	10MHz	10MHz
1Hz	-67 dBc	-108 dBc
10Hz	-95 dBc	-130 dBc
100Hz	-125 dBc	-140 dBc
1 kHz	-135 dBc	-155 dBc
10KHz	-145 dBc	-155 dBc

### Harmonics

	Options C
Frequency	10MHz
	<-30dBc
	<-45dBc

### Spurious

100 KHz BW	<-100dBc
------------	----------

### Aging (After 30 days)

Frequency	10MHz
Per day	$5 \times 10^{-12}$
Per Month	$5 \times 10^{-11}$
Per Year	$5 \times 10^{-10}$

### Frequency accuracy

Accuracy at shipping  $5 \times 10^{-11}$

### Frequency retrace

After 1 hours of continues operation  $8 \times 10^{-11}$

### Frequency Adjustment

Mechanical POT  $\pm 2 \times 10^{-9}$  (Control voltage 0 to +5V)

### Warm up time

<6 minutes, time to lock

<7 minutes to  $1 \times 10^{-10}$  at room temperature 25°C

### Battery operation

Battery running time at full charge at +20°C: >10 hours

Charging time: 7-8 hours

### Environmental

Temperature :	Operating	-40°C +65°C
	Storage	-40°C +80°C
	-20°C +60°C	$< 1 \times 10^{-9}$

### Temp stability :

Standard	-20°C +60°C	$< 0.3 \times 10^{-9}$
Option E	-30°C +65°C	$0.5 \times 10^{-9}$
Option F	-50°C +65°C	$0.7 \times 10^{-9}$

Relative humidity : 90% non-condensing

Magnetic Field sensitivity :  $3 \times 10^{-11}$  Gauss

Atmospheric pressure : -60m -4000m  $< 2 \times 10^{-11}$  Per mbar

Approximate MTBF : 100,000 Hrs, Stationary

Dimensions : 122 x 105 x 60mm LWH

Without battery >600gms

With internal battery >700gms

Power supply	Standard	Option X
DC power:	External +12	+5.5V

Power consumption: 18W at start (25°C), 8W at steady state    5.2W at start (25°C), 1.6W at steady state

### Built-in options

- Option 02:** Output 2048kHz
- Option 03:** Output 1544kHz
- Option 04:** 13MHz Output
- Option 05:** CMOS/TTL Output
- Option 06:** 1PPS Output
- Option 07:** 10.24MHz Output
- Option 08:** 10.23MHz Output
- Option 09:** Increase 2, 4, 6 or 8 output distribution card
- Option 10:** 26MHz Output
- Option 11:** 1MHz Output
- Option 12:** 5MHz Output
- Option 18:** Extend warranty to 3 years
- Option 20:** External synch input. 1PPS, 5MHz or 10MHz
- Option 21:** 2 x 1PPS Output
- Option 42:** Low Phase Noise 10MHz output
- Option 52:** Rack Mount 19" 1U
- Option 53:** Rack Mount 19" 2U
- Option 75:** Add internal battery, up to 4 hours of battery life.

**Included with shipment:** Calibration certificate, Certificate of Conformance, product test sheet and 24 month warranty.

Contact us to configure this product to meet your requirement.  
Designed and manufactured in the U.K.

The Quartzlock logo is a registered trademark.

Quartzlock continuous improvement policy: spec subject to change without notice and not part of any contract.

Copyright © 2018. Issue 18.01